

HHB

HAND HOLE CIRCUIT BREAKER

FEATURES

Pedestal Enclosure fits into most concrete pole manufacturers hand hole . The Hand Hole Breaker is 9" Tall, 2" Wide and 4" Deep.

Delivered "Ready to Install" with a Service Entrance rating, 22kA I.C. series rating, and ESA approval.

Completely pre-wired & is NEMA 3R Tested and backed by a 10 year warranty.

CONSTRUCTION

#6 AWG line and load conductors on 50A units

#10 AWG line and load conductors on 15A units.

#14 AWG load conductor for feeding the light.

Constructed to prevent weather intrusion without the means of a rubber gasket.



BREAKER OPTIONS CHART

CAT. No.	DESCRIPTION	BREAKER	DIMENSIONS
SL115	120 VOLT IN-POLE PANEL	SINGLE POLE 15 AMP	225mm H x 57mm W x 105mm
SL150	120 VOLT IN-POLE PANEL	SINGLE POLE 50 AMP	225mm H x 57mm W x 105mm
SL215	120 VOLT IN-POLE PANEL	TWO POLE 15 AMP	225mm H x 57mm W x 105mm
SL250	120 VOLT IN-POLE PANEL	TWO POLE 50 AMP	225mm H x 57mm W x 105mm

DISTRIBUTED BY:

